

TRACK DRILLS (DLD 1200)



ADDED FEATURES

- Cyclone & Rotary Splitter (attached)
- Gilson Sample Splitter
- 150 gal. Mud Tanks
- 2in. Diaphragm Pump
- B.O.P. Casing diverter

SUPPORT EQUIPMENT

- 4 X 4 Crew Vehicle
- IHC 4x4 Rig Tender
 - 900 gal. Water Capacity
 - 200 gal. Additional Fuel Capacity
 - Hydraulic Loading Pumps
 - 1,200 ft Pipe Carrying Capacity
 - Additional Tool Storage
 - Welders & Torches

SPECIFICATIONS

DRILL RIG DIMENSIONS

WIDTH	9 ft.
LENGTH	18 ft.
WEIGHT	52,100 lbs

CLEARANCE

HEIGHT	
DERRICK UP	24 ft.
DERRICK DWN	11 ft.

MAX. DEPTH	1,200 ft.
DRILL PIPE SIZE	4in.
HOLE DIAM.	4.5in - 5.25in
PULLBACK	30,000 lbs.
PULLDOWN	15,000 lbs.
WINCH	8,000 lbs.
ROTARY TORQUE	6,500 ft lbs.
ROTARY SPEED	0-100 rpm.
COMPRESSOR	900cfm x 350psi
WATER INJECTION	0-10 gpm
TRACK SYSTEM	24" tracks
GROUND PRESS.	7.5 psi
GROUND SPEED	8 mph.
GRADEABILITY	70% slope
DECK LEVELING	45% slope
STABILIZER JACKS	Rear, 24" Stroke
DOZER BLADE	Hyd. w / tilt



DIVERSIFIED DRILLING LLC.